



The power behind your lights

ZHUHAI JINBO KECHUANG ELECTRONICS CO., LTD.

163 Xiaolin Road, Hongqi, Jinwan, Zhuhai, Guangdong, China

Tel: +86-756-2256343 Fax: +86-756-3820283

E-mail: info@zhjb.com www.zhjb.com



Brief Information

Super-Thin Series

100W

Waterproof Power Supply (C.V.)

Model JLV-12100PA-EF / JLV-24100PA-EF

Input 220-240V AC

Output 12VDC 8.33A 100W/ 24VDC 4.17A 100W

Product Features

- Plastic housing, LPV standard
- High transfer efficiency
- Super-thin: 18mm height
- High Power Factor: PF>0.95
- Glue filled, anti-moisture
- 100% full loading, 100% burn-in tested
- Overload/short circuit protection
- Standby power consumption < 0.5W

* Defogger complaint version is available subject to request

Model: JLV-12100PA-EF Size: 220x68x18mm
JLV-24100PA-EF



MAIN ELECTRICAL DATA

AC Input

Input Voltage	220-240V (Rated Range) 185-250V (Workable Range)
Input Frequency	50/60Hz
Efficiency (Typ.)	>88%
Input Current	220V: 0.6A max.
Inrush Current	75A
Leakage Current	5mA/220VAC

DC Output

Output Voltage	12V	24V
Rated Current	8.3A	4.17A
Rated Power	100W	100W
Ripple & Noise (Max.)	<150mVp-p	<150mVp-p
Setup, Rise Time	1500ms/220VAC	1500ms/220VAC
Line Regulation	1%	1%
Load Regulation	1%	1%

Service Environment

Working Temp.	-25°C~70°C (Derating from 50°C)
Working Humidity	15~99%RH
Storage Temp.	-40°C~80°C
Storage Humidity	10~99%RH

Standards

EN 55015:2019+A11:2020	
EN 61347-2-13:2014+A1:2017	EN 61000-3-2:2019+A1:2021
EN 61347-1:2015+A1:2021	EN 61000-3-3:2013+A1:2019+A2:2021
EN 62493:2015	EN 61547: 2009

Protection

Overload	Yes, cut-off when loading exceeds 10-40%
Short Circuit	Yes, hiccup mode, recovers automatically after fault condition is removed

Safety

Safety Standard	EN 61347-2-13
Withstand Voltage	I/P-O/P: 3KV AC; O/P-GND: 0.5KV AC
Isolation Resistance	I/P-O/P: >100M Ohms / 500VDC /25°C / 70%RH

Packaging Information

Product Dimension	220*68*18mm
Products Net Weight	480G
PCS/Carton(QTY)	30 PCS
Master Carton Size	36.5*28.5*25cm
G. Weight/ Carton	16KG


Installation Tips:

- Please identify the power supply's input and output before installation.
- Ensure correct output + & - wire connection.
Power on after wire connection is done.
- To avoid voltage drop and loading capacity wasting on the output extension wire, please install the power supply to the loading as near as possible, if must use long extension wires, thicker wires and less loading wattage is required.
- The power supply to be installed at good ventilation and cooling environment.

Ref. file No. 100PA-EFES3

All data are for reference only, subject to revise without prior notice.

Physical Drawing



Brief Information

Super-Thin Series

100W

Waterproof Power Supply (C.V.)

Model JLV-12100PA-EF / JLV-24100PA-EF

Input 220-240V AC


Output 12VDC 8.33A 100W/ 24VDC 4.17A 100W

Input: 2x1mm² wire, Brown L, Blue N
150mm length


Output: 2x16AWG wire, Red +, Black -
170mm length

Housing: Plastic (ABS)

Block Diagram



Derating Curve



Static Characteristics

